


SWITCH STYLE NO.	RATINGS					POST INSUL NEMA TR*	DIMENSIONS IN INCHES								WEIGHT/POLE INCL. INSUL.	
	kV NOM	kV MAX	kV BIL	AMPS	kA MOM		MILLIMETERS SHOWN IN ()								LBS.	(KG)
							"A"	"B"	"C"	"D"	"E"	"F"	"G"	"H"		
C06B039G01 C06B039G02 C06B039G03	115	123	550	600	40	286	57.78 (1468)	45 (1143)	62 (1575)	60 (1524)	52 (1321)	126.84 (3222)	.50 (13)	7 (178)	880 (400)	(406)
1200				61	893 (406)							902 (410)				
1600				70	907 (412)							932 (424)	957 (435)			
C06B039G04 C06B039G05 C06B039G06	138	145	650	2000	100	288	58.03 (1474)	54 (1372)	66.81 (1700)	70 (1778)	62 (1575)	128.53 (3265)	.75 (19)	7 (178)	907 (412)	932 (424)
2500				100	932 (424)							957 (435)				
3000				120	957 (435)							1007 (458)	1033 (470)	1049 (477)		
C06B039G07 C06B039G08 C06B039G09	161	170	750	600	40	291	74.78 (1899)	62 (1575)	70.19 (1783)	78 (1981)	70 (1778)	145.84 (3704)	.50 (13)	7 (178)	970 (441)	982 (446)
1200				61	1002 (455)							1007 (458)				
1600				70	1007 (458)							1033 (470)	1049 (477)			
C06B039G10 C06B039G11 C06B039G12	161	170	750	2000	100	291	75.03 (1905)	62 (1575)	70.19 (1783)	78 (1981)	70 (1778)	147.53 (3747)	.75 (19)	7 (178)	1007 (458)	1033 (470)
2500				100	1033 (470)							1049 (477)				
3000				120	1049 (477)							1062 (483)	1075 (488)	1090 (495)		
C06B039G13 C06B039G14 C06B039G15	161	170	750	600	40	291	74.78 (1899)	62 (1575)	70.19 (1783)	78 (1981)	70 (1778)	161.84 (4111)	.50 (13)	7 (178)	1062 (483)	1075 (488)
1200				61	1075 (488)							1090 (495)				
1600				70	1090 (495)							1095 (498)	1120 (509)	1145 (520)		
C06B039G16 C06B039G17 C06B039G18	230	245	900	2000	100	304	75.03 (1905)	80 (2032)	74.25 (1886)	94 (2388)	86 (2184)	163.53 (4154)	.75 (19)	10 (254)	1095 (498)	1120 (509)
2500				100	1120 (509)							1145 (520)				
3000				120	1145 (520)							1429 (650)	1444 (656)	1449 (658)		
C06B039G19 C06B039G20 C06B039G21	230	245	900	600	40	304	94.78 (2407)	80 (2032)	74.25 (1886)	94 (2388)	86 (2184)	199.41 (5065)	.50 (13)	10 (254)	1429 (650)	1444 (656)
1200				61	1444 (656)							1449 (658)				
1600				70	1449 (658)							1456 (662)	1481 (673)	1512 (687)		
C06B039G22 C06B039G23 C06B039G24	230	245	900	2000	100	304	95.03 (2414)	80 (2032)	74.25 (1886)	94 (2388)	86 (2184)	201.16 (5109)	.75 (19)	10 (254)	1456 (662)	1481 (673)
2500				100	1481 (673)							1512 (687)				
3000				120	1512 (687)											



NOTES:
 1. ALUMINUM TERMINAL PADS.
 2. INSULATORS INVERTED FOR UNDERHUNG MOUNTING. (SEE NOTE 7)
 3. CUSTOMER TO SUPPLY "X" & "Y" DIMENSIONS.
 4. ALL DIMENSIONS ARE IN INCHES.
 5. DIMENSIONS IN () ARE IN MM.
 6. WEIGHTS IN () ARE IN KG.
 7. SWITCH STYLE NUMBERS SHOWN WITH ☒, ARE NOT AVAILABLE IN UNDERHUNG MOUNTING CONFIGURATION.

REVISION
 A - UPDATE "Y" INSUL. MTC BRACKETS MD. 3/12/04
 B - UPDATE MAX KV LAB 9/2/04

REV B	Cleaveland/Price, Inc. 1400 Route 993 : Trafford, PA. 15085			SCALE: PROPORTIONAL
CODE A	DRAWN: PMK	CHECKED: GH	DATE: 10-28-03	DWG NO. C06B039
V2-CA ALUMINUM VERTICAL BREAK SWITCH WITH INCLINED INSULATOR 115kV-230kV-900BIL; 600A-3000A				