

1. ALUMINUM BLADES, TIN PLATED COPPER TERMINALS.
2. ALL DIMENSIONS ARE IN INCHES.
3. DIMENSIONS IN [] ARE MM.
4. CUSTOMER TO SUPPLY "X" AND "Y" DIMENSIONS.

TERMINAL DIMENSIONS TYPICAL EACH END

Ø.56 [Ø14] (12) EA. TERM.

R75 [R1905]

R67 [R1702]

FINGER END

STAB END

**RIGHT HAND SWING AS SHOWN
LEFT HAND SWING OPP. HAND**

CORONA RING/ICE SHIELD

**116 [2946]
OPEN GAP**

**TR-324
POST
INSULATORS**

**INTERPHASE
DRIVE PIPE
ON THIS END
OF SWITCH**

**Ø.69 [17]
MOUNTING
HOLES**

FINGER END

STAB END

"X"

"Y"

8.5 [216]

126 [3200]

143 [3632]

8.25 [210]

8.5 [216]

127.84 [3247]

7.63 [194]

1.25 [32]

1.75 [44]

6 [152]

1.75 [44]

6 [152]

3.7 [10]

1.5 [38]

1.75 [44]

106 [2692]

14.22 [361]

MOM kA.	100	120
WT./POLE	1550 lbs. 703 kg.	1470 lbs. 668 kg.

**CODE
A-00**

C26A307