



	VOLTAGE	OP. TIME	THRUST (MIN)	PIPE SIZE
G01	125 D.C.	0.5 SEC.	SEE TABLE - A	PIVOT, 1" DIA. OR 1.25" IPS
G02	120 A.C.	0.5 SEC.	SEE TABLE - A	PIVOT, 1" DIA. OR 1.25" IPS
G03	240 A.C.	0.5 SEC.	SEE TABLE - A	PIVOT, 1" DIA. OR 1.25" IPS
G04	125 D.C.	0.8 SEC.	SEE TABLE - B	PIVOT, 1" DIA. OR 1.25" IPS
G05	120 A.C.	0.8 SEC.	SEE TABLE - B	PIVOT, 1" DIA. OR 1.25" IPS
G06	240 A.C.	0.8 SEC.	SEE TABLE - B	PIVOT, 1" DIA. OR 1.25" IPS
G07	48 D.C.	0.5 SEC.	SEE TABLE - A	PIVOT, 1" DIA. OR 1.25" IPS
G08	48 D.C.	0.8 SEC.	SEE TABLE - B	PIVOT, 1" DIA. OR 1.25" IPS
G09	24 D.C.	0.5 SEC.	SEE TABLE - A	PIVOT, 1" DIA. OR 1.25" IPS
G10	24 D.C.	0.8 SEC.	SEE TABLE - B	PIVOT, 1" DIA. OR 1.25" IPS
G11	250 D.C.	0.5 SEC.	SEE TABLE - A	PIVOT, 1" DIA. OR 1.25" IPS
G12	250 D.C.	0.8 SEC.	SEE TABLE - B	PIVOT, 1" DIA. OR 1.25" IPS

	STROKE	THRUST (MIN)
A	7.75"	1400 LBS
	13.5"	800 LBS
B	7.75"	1600 LBS
	13.5"	1000 LBS

MOTOR OPERATOR WEIGHT = 118 LBS (54KG)

REVISION								
REV	D	Cleaveland/Price Inc. 1400 Route 993 : Trafford, PA 15085						
VERSION		2	DRAWN JKA	CHECKED CMC	APPROVED	DATE 08/28/1996	SHEET 1 OF 1	SCALE PROPORTIONAL
TYPE RP-C2 MOTOR OPERATOR OUTLINE								DWG. NO. C11B002