

GROUP NO.	RATINGS					POST INSULATOR NEMA TR #	DIMENSIONS IN INCHES MILLIMETERS SHOWN IN []								WEIGHT/POLE (INCLUDING INSULATORS)	
	kV NOM.	kV MAX.	kV BIL	AMPS	kA MOM.		"A"	"B"	"C"	"D"	"E"	"R1"	"R2"	lbs.	kg.	
G01	230	245	900	1600	70	304	101.85 [2587]	80 [2032]	113.00 [2870]	96.00 [2438]	84.00 [2134]	54.80 [1392]	50.81 [1291]	1236	[561]	
G02	230	245	1050			312	113.85 [2829]	92 [2337]	131.00 [3327]	114.00 [2896]	104.00 [2642]	63.80 [1621]	59.81 [1519]	1398	[635]	
G03	230	245	900	2000	100	304	101.85 [2587]	80 [2032]	113.00 [2870]	96.00 [2438]	84.00 [2134]	54.80 [1392]	50.81 [1291]	1248	[567]	
G04	230	245	1050			312	113.85 [2829]	92 [2337]	131.00 [3327]	114.00 [2896]	104.00 [2642]	63.80 [1621]	59.81 [1519]	1413	[642]	

NOTES:

SWITCH STYLE REFERENCE NUMBER		REV
N/A		E
DRAWN	DATE	VERSION
LAB	10/02/2001	1
CHECKED	DRAWING NO.	
DP	C26A026	
APPROVED		