

RTU	N/A
RADIO	N/A
CHARGER	5A @ 120 A.C.
HEATER	100W @ 125V
SPEED	4.0 SEC. @ 90 DEG.
IN. LBS. TORQUE MIN.	2,500
PREFERED DIRECTION	C.W. OR C.C.W.
SCHEMATIC	C128B996

ITEM	DESCRIPTION	STYLE NO.	G001
H001	MAIN ASSEMBLY	C133D019G001	1
H002	CONTROL MODULE ASSEMBLY	C128A150G001	1
H003	POWER MODULE ASSEMBLY	C128A151G004	1
H004	ACCESS COVER ASS'Y	C413A222G001	1
H005	RTU PANEL ASS'Y	C133B122G001	1
R200	ENCLOSURE	C139C065G001	1
R205	AB CHANCE MOUNTING ASS'Y	C132A033G001	1
R210	S&C MOUNTING KIT	C132A036G001	1

NOTE: IF AUTOMATING MORE THAN ONE WAY OF A PADMOUNT SWITCH, YOU MAY USE "DRONE" CB33AA04 AS ADDITIONAL UNITS. FOR AN A.B. CHANCE 15KV AIS-10 SWITCH, ALWAYS HANG THIS "MASTER" TO THE RIGHT SIDE OF A "DRONE" UNIT.

